# **SOLIDEAL MAGNUM NM** BY CAMSO



RESILIENT



### OPTIMAL NON-MARKING RESILIENT SOLUTION FOR MEDIUM INTENSITY APPLICATIONS

The preferred solution for medium intensity applications requiring non-marking resilient tires. Its wide profile, flat footprint and proven tread design provide maximum reliability, stability and traction. Its clean running makes this tire the ideal solution for indoor operations and rental fleets. USAGE INTENSITY



PERFORMANCE

ENERGY SAVINGS







camso.co

## **RESILIENT TIRES**

# SOLIDEAL MAGNUM NM

TIRE SIZE	RIM SIZE <sup>(1)</sup>	HEEL	
3.00-4	2.10-4	NORMAL	QUICK
3.00-4	2.50C-4		
4.00-4	2.50C-4		
4.00-8	3.00D-8		
5.00-8	3.00D-8		
5.00-8	3.50-8		
<b>15x4 1/2-8</b> (125/75-8)	3.00D-8	-	•
<b>15x4 1/2-8</b> (125/75-8)	3.251-8		
<b>16x6-8</b> (150/75-8)	4.33R-8		
<b>18x7-8</b> (180/70-8)	4.33R-8	-	
140/55-9	4.00E-9		
6.00-9	4.00E-9		
<b>21x8-9</b> (200/75-9)	6.00E-9		
200/50-10	6.50F-10		=
6.50-10	5.00F-10	•	
<b>23x9-10</b> (225/75-10)	6.50F-10		
<b>23x10-12</b> (250/60-12)	8.00G-12		
<b>27x10-12</b> (250/75-12)	8.00G-12		
7.00-12	5.00S-12		
<b>150/100-13</b> (23x5)	3.75P-13		
<b>28x9-15</b> (8.15-15 & 225/75-15)	7.00-15		
355/50-15	9.75-15		
<b>355/65-15</b> (32x12.1-15)	9.75-15		
<b>250-15</b> (250/70-15)	7.00-15	-	•
<b>250-15</b> (250/70-15)	7.50-15		
<b>300-15</b> (315/70-15)	8.00-15		•
310-15 EW	8.00V-15		
7.00-15	5.50-15		•
8.25-15	6.50-15		
9.00-20	7.00-20		
10.00-20	7.50-20		
10.00-20	8.00-20		
11.00-20	8.00-20		
12.00-20	8.00-20		
12.00-20	8.50-20		
14.00-24	10.00-24IRA		





Remarks

(1) Check rim for size, especially on width, as this should correspond to tirebase marking. Check also max. load of rim with rim manufacturer, as wheel load will be restricted by lowest load capacity, either the one given by the rim or by the tire.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.

#### camso.co

