

SOLIDEAL RES 550 MAGNUM SERIE

BY CAMSO



RESILIENT



MAXIMUM LIFESPAN FOR MEDIUM INTENSITY APPLICATIONS

The standard in reliability and the longest lasting tire in the industry for medium intensity applications*. Its wide profile and flat footprint designed to maximize life. Its large tread blocks and deep lugs increase traction, while delivering maximum stability.

camso.co

USAGE INTENSITY



PERFORMANCE



ENERGY SAVINGS



TIRE LIFE



COMFORT



RESILIENT TIRES

SOLIDEAL RES 550 MAGNUM BY CAMSO SERIE

TIRE SIZE	RIM SIZE ⁽¹⁾	HEEL	
		NORMAL	QUICK
3.00 - 4	2.10-4	■	
3.00 - 4	2.50C-4	■	
4.00 - 4	2.10-4	■	
4.00 - 4	2.50C-4	■	
4.00 - 8	3.00D-8	■	■
5.00 - 8	3.00D-8	■	■
5.00 - 8	3.50-8	■	
15 x 4 1/2 - 8 (125/75-8)	3.00D-8	■	■
15 x 4 1/2 - 8 (125/75-8)	3.25I-8	■	
16 x 6 - 8 (150/75-8)	4.33R-8	■	■
18 x 7 - 8 (180/70-8)	4.33R-8	■	■
18 x 9 - 8	7.00E-8	■	
140 / 55 - 9	4.00E-9		■
6.00 - 9	4.00E-9	■	■
21 x 8 - 9 (200/75-9)	6.00E-9	■	■
200 / 50 - 10	6.50F-10	■	■
6.50 - 10	5.00F-10	■	■
6.50 - 10	5.50F-10	■	
23 x 9 - 10 (225/75-10)	6.50F-10	■	■
7.50 - 10	5.00F-10	■	
7.50 - 10	5.50F-10	■	■
23 x 10 - 12 (250/60-12)	8.00G-12	■	■
27 x 10 - 12 (250/75-12)	8.00G-12	■	■
7.00 - 12	5.00S-12	■	■
8.25 - 12	5.00S-12	■	
150 / 100 - 13 (23x5)	3.75P-13	■	■
28 x 9 - 15 (8.15-15 & 225/75-15)	6.50-15	■	
28 x 9 - 15 (8.15-15 & 225/75-15)	7.00-15	■	■

TIRE SIZE	RIM SIZE ⁽¹⁾	HEEL	
		NORMAL	QUICK
355 / 50 - 15	9.75-15	■	■
355 / 65 - 15 (32x12.1-15)	9.75-15	■	■
250 - 15 (250/70-15)	7.00-15	■	■
250 - 15 (250/70-15)	7.50-15	■	■
300 - 15 (315/70-15)	8.00-15	■	■
310 - 15 EW	8.00V-15	■	
5.50 - 15	4.50E-15SDC	■	
6.00 - 15	4.50E-15SDC	■	
7.00 - 15	5.50-15	■	■
7.00 - 15	6.00-15	■	
7.50 - 15	5.50-15	■	■
7.50 - 15	6.00-15	■	
7.50 - 15	6.50-15	■	■
8.25 - 15	5.50-15	■	■
8.25 - 15	6.50-15	■	■
7.50 - 16	6.00-16	■	
9.00 - 20	7.00-20	■	
10.00 - 20	6.50-20	■	
10.00 - 20	7.00-20	■	
10.00 - 20	7.50-20	■	
10.00 - 20	8.00-20	■	
11.00 - 20	7.50-20	■	
11.00 - 20	8.00-20	■	
12.00 - 20	8.00-20	■	
12.00 - 20	8.50-20	■	
14.00 - 24	10.00-24IRA	■	
14.00 - 25	11.25-25	■	
16.00 - 25	11.25-25	■	



WIDE PROFILE AND FLAT FOOTPRINT

- Increases stability and grip

LARGE TREAD BLOCKS AND DEEP LUGS

- Maximizes life and traction

ESTABLISHED TREAD PATTERN DESIGN

- Proven reliability for over 25 years

EXCEPTIONAL TREAD RUBBER COMPOUND PROPERTIES

- Make this tire the longest lasting tire in the industry for medium intensity applications*

60J LINE

- Ensures maximum tire utilization



*Based on internal tests

AVAILABLE IN NON-MARKING



Remarks

(1) Tolerances on wheel diameter • Code designated sizes (in): nominal rim diameter +0.005"/-0" • Metric sizes (mm): h11 according to ISO/R286.
Surface roughness Ra < 6.3 µm • Chamfer 5 mm wide @ 30°

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.

camso.co

1910_MH_RES_ProdSheet_RES550_A4_EN_V3 - PRINTED IN CANADA

