SOLIDEAL AIR 570 BY CAMSO





LOW ROLLING RESISTANCE SOLUTION FOR ELECTRIC TRUCKS

Best all-around pneumatic tyre for electric forklifts. Engineered to deliver low rolling resistance and reduced vibrations for optimal performance.

PERFORMANCE

TYRE LIFE

DINCTURE RECIETANCE

PUNCTURE RESISTANCE

STABILITY



INDUSTRIAL PNEUMATIC TYRES

SOLIDEAL AIR 570

TYRE SIZE	PR	TUBE* & VALVE**	FLAP	RIM SIZE ⁽¹⁾	
				Recommended	Alternative
5.00-8	8	JS2	90 - 8	3.00 D	3.25l/3.75l
15 x 4 1/2-8	12	JS2	90 - 8	3.00 D	3.25l
16 x 6-8	10	V3-02-5	130 - 8	4.33 R	-
18 x 7-8	14	V3-02-07	130 - 8	4.33 R	5.00F
18 x 7-8	16	V3-02-07	130 - 8	4.33 R	5.00F
6.00-9	10	JS2	125 - 9	4.00 E	-
21 x 8-9	16	JS2	180 - 9	6.00 E	7.00E
23 x 9-10	16	JS2	180 - 10	6.50 F	-
23 x 9-10	18	V3-02-07	180 - 10	6.50 F	-
28 x 9-15	14	TR75A	180 - 15 HD	7.00	-
28 x 9-15	18	V3-02-08	180 - 15 HD	7.00	-



FLATTREAD PROFILE

 Enhances stability and provides even tyre wear

RIB PATTERN AND LOW-ABRASION COMPOUND

 Provides low rolling resistance for best energy efficiency



SMOOTH CONTINUOUS CENTRE LUG

 Reduces vibration and provides enhanced streerability

REINFORCED CARCASS AND SIDEWALL

 Provides additional puncture resistance to prevent flat tyres

Remarks

- Consult tyre and wheel manufacturer for confirmation of the suitability of the tyre/rim combination particularly with regard to rim profile and wheel strength.
- (2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. Loads apply to cyclic service applications. Cyclic service means applications where tyre are not used continuously at the load indicated by its Load Index and Speed Symbol. It does not refer to the length of time a vehicle is in use. but rather that there is a variation in load and/or speed.
- * Tube size is identical to tyre size
- ** Table shows standard valves. Other valves on request.

NHS – Not for Highway Service: Tyres primarily designed for use outside of public roads, but suitable for temporary/incidental use on public roads.

All tyres come with tube and flap.

It is possible that certain items are not sold in your region.

 $\label{lem:please contact} \textbf{Please contact your local sales contact to check tyre availability in your region.}$

