

# SOLIDEAL RES 330

BY CAMSO



RESILIENT



## LONGEST LASTING TYRE IN THE INDUSTRY FOR LOW INTENSITY APPLICATIONS

Best-in-class tyre for low intensity applications\*. A high performing tread rubber compound makes this tyre a unique long lasting tyre. Wide, aggressive tread with natural rubber compounds extends its life while resisting cutting and chunking. A steel-bead reinforced heel means the tyre won't slip on the rim.

[camso.co](http://camso.co)

## PERFORMANCE

ENERGY SAVINGS



TYRE LIFE



COMFORT



## RESILIENT TYRES

# SOLIDEAL RES 330

BY CAMSO

TYRE SIZE	RIM SIZE <sup>(1)</sup>	HEEL	
		NORMAL	QUICK
5.00-8	3.00D-8	■	■
15x4 1/2-8 (125/75-8)	3.00D-8	■	■
16x6-8 (150/75-8)	4.33R-8	■	■
18x7-8 (180/70-8)	4.33R-8	■	■
140x55-9	4.00E-9	■	■
6.00-9	4.00E-9	■	■
21x8-9 (200/75-9)	6.00E-9	■	■
200/50-10	6.50F-10	■	■
6.50-10	5.00F-10	■	■
23x9-10 (225/75-10)	6.50F-10	■	■
23x10-12 (250/60-12)	8.00G-12	■	■
27x10-12 (250/75-12)	8.00G-12	■	■
7.00-12	5.00S-12	■	■
28x9-15 (8.15-15 & 225/75-15)	7.00-15	■	■
355/45-15 (28x12.5-15)	9.75-15	■	■
355/65-15 (32x12.1-15)	9.75-15	■	■
250-15 (250/70-15)	7.00-15	■	■
205-15 (250/70-15)	7.50-15	■	■
300-15 (315/70-15)	8.00-15	■	■
7.00-15	5.50-15	■	■
7.50-15	6.50-15	■	■
8.25-15	6.50-15	■	■
10.00-20	7.50-15	■	■
10.00-20	8.00-20	■	■





**WELL BALANCED RUBBER COMPOUND**

- ☒ Operate in low intensity applications and offer the lowest operating cost

**AGGRESSIVE DEEP TREAD DESIGN**

- ☒ Provide great traction and stability



**EXCEPTIONAL TREAD RUBBER COMPOUND PROPERTIES**

- ☒ Make this tyre the longest lasting tyre in the industry for low intensity applications\*

**STEEL BEAD REINFORCED HEEL**

- ☒ Prevents rim slip

**WEAR INDICATOR**

- ☒ Ensures maximum tyre utilization

**Remarks**

- (1) Check rim for size, especially on width, as this should correspond to tirebase marking. Check also max. load of rim with rim manufacturer, as wheel load will be restricted by lowest load capacity, either the one given by the rim or by the tyre.
- (2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. Loads apply to cyclic service applications. Cyclic service means applications where there is a variation in load and/or speed.

For further details, please consult the technical department.

Loads are valid for intermittent service only. Intermittent service means a minimum load variation of 2.5. Does not include the additional weight of the solid tyre when converting from pneumatics.

**This document contains technical data of all products globally.**

**It is possible that certain items are not sold in your region.**

**Please contact your local sales contact to check tyre availability in your region.**

