



# SOLIDEAL RES 660 XTREME SERIES

BY CAMSO



RESILIENT



## MAXIMUM LIFESPAN FOR HIGH INTENSITY APPLICATIONS

The ultimate tire for high intensity use. The Solideal RES 660 runs at overall lower operating temperatures to withstand non-stop usage and high load environments. A high performing abrasion resistant tread rubber compound makes this tires the longest lasting tire in the industry\*. Low energy use and low vibration level is also making this tire the ideal solution for electrical forklift equipment.

[camso.co](http://camso.co)

### USAGE INTENSITY



### PERFORMANCE

#### ENERGY SAVINGS



#### TIRE LIFE



#### COMFORT



[camso.co](http://camso.co)



# SOLIDEAL RES 660 XTREME SERIES

BY CAMSO



TIRE SIZE	RIM SIZE <sup>(1)</sup>	HEEL	
		NORMAL	QUICK
5.00-8	3.00D-8	■	■
15x4 1/2-8 (125/75-8)	3.00D-8	■	■
16x6-8 (150/75-8)	4.33R-8	■	■
18x7-8 (180/70-8)	4.33R-8	■	■
140/55-9	4.00E-9	■	■
6.00-9	4.00E-9	■	■
21x8-9	6.00E-9	■	■
180/60-10	5.00F-10	■	■
200/50-10	6.50F-10	■	■
6.50-10	5.00F-10	■	■
23x9-10 (225/75-10)	6.50F-10	■	■
23x10-12 (250/60-12)	8.00G-12	■	■
23x12-12 (315/45-12)	10.00G-12	■	■
27x10-12 (250/75-12)	8.00G-12	■	■
7.00-12	5.00S-12	■	■
28x9-15 (8.15-15 & 225/75-15)	7.00-15	■	■
355/45-15 (28x12.5-15)	9.75-15	■	■
355/50-15	9.75-15	■	■
355/65-15 (32x12.1-15)	9.75-15	■	■
250-15 (250/70-15)	7.00-15	■	■
250-15 (250/70-15)	7.50-15	■	■
300-15 (315/70-15)	8.00-15	■	■
7.00-15	5.50-15	■	■
7.00-15	6.00-15	■	■
7.50-15	5.50-15	■	■
7.50-15	6.00-15	■	■
7.50-15	6.50-15	■	■
8.25-15	5.50-15	■	■
8.25-15	6.50-15	■	■
400/60-15	11.00 - 15	■	■

TIRE SIZE	RIM SIZE <sup>(1)</sup>	HEEL	
		NORMAL	QUICK
7.50 - 16	6.00-16	■	■
355 / 50 - 20	10.00-20	■	■
9.00 - 20	7.00-20	■	■
10.00 - 20	7.00-20	■	■
10.00 - 20	7.50-20	■	■
10.00 - 20	8.00-20	■	■
12.00 - 20	8.00-20	■	■
12.00 - 20	8.50-20	■	■
12.00 - 20	10.00-20	■	■
12.00 - 20 EW	10.00-20	■	■
465 / 55 - 20	16.00-20	■	■
12.00 - 24	8.50-24	■	■

**CONTINUOUS CENTER LUG**

- Reduces vibration which lowers heat build-up and increases life.
- Increases operator comfort and slows wear on driveline components

**EXCEPTIONAL TREAD RUBBER COMPOUND PROPERTIES**

- Make this tire the longest lasting tire in the industry for high intensity applications\*



**WIDE TREAD PROFILE**

- Increases lateral load stability
- Safer in high-lift and cornering situations

**WEAR INDICATOR**

- Ensures maximum tire utilization

**COOL RUNNING RUBBER COMPOUNDS**

- Withstand high usage intensity and offer low energy consumption

AVAILABLE IN NON-MARKING AND NON-MARKING ANTI-STATIC



AUTHORIZED DISTRIBUTOR: